



# RPB Series Pendant Station - Rubber Enclosures


One-Speed and Two-Speed Control plus Accessories  
With Standard Cord Grip



RP-4



RP-3



RP-2



RP-1

## Dimensions and Weights

Enclosure Size	Dimension-Inches			Weight Lbs.	Accommodates Cable Diameter (Inches*)
	Width	Depth	Length		
Two-Button	3	2-1/2	5-3/4	1-3/4	.437 - .740
Four-Button	3	2-1/2	9	2-3/4	.437 - .740
Six-Button	3	2-1/2	12-3/8	3-1/2	.437 - .740
Eight-Button	3	2-5/8	15-3/4	4-1/4	.640 - .875

\* Specify Cable Diameter when the Cable Used is not within the Range Listed.

RPB Series Pushbutton Pendant Stations feature steel reinforced rubber construction with a tongue and groove cover plate to protect buttons from many elements. The RPB Series support a number of applications with single and two speed operation, momentary and maintained switches, and a variety of accessory and replacement parts. Wire mesh grips for added strain relief are available.

- Nitrile Rubber Construction
- NEMA 1, 3, 4 and 12
- UL Listed and CSA Approved

## Enclosures

Each complete enclosure includes a standard package of legend plates, cord grip and strain relief bracket.

RP-1	Two-Button
RP-2	Four-Button
RP-3	Six-Button
RP-4	Eight-Button

## Front Covers Only (including Legend Plate Package)

RP-1F	Two-Button
RP-2F	Four-Button
RP-3F	Six-Button
RP-4F	Eight-Button

Pictures are for illustration purposes and may not represent actual product.  
Duct-O-Wire® recommends installation of an Emergency Stop on all Pendants.

