



RPS Series Pendant Station - Rubber Enclosures

One-Speed through Five-Speed Control plus Accessories
With Standard Cord Grip



RPS-3

Eight Button - Three Motion plus Accessory Area

Each enclosure includes a standard package of legend plates, cord grip, neoprene boots and provision for a strain relief bracket. The top accessory area will accept any two-button insert or any two accessories.

- Nitrile Rubber Construction
- NEMA 1, 3 and 12
- CSA Approved

***Drilling of Accessory Area may be required.**

Dimensions and Weights					
Enclosure Catalog Number	Dimensions - Inches			Weight Lbs.	Accommodates Cable Diameter (Inches)
	Width	Depth	Length		
RPS-3	4	2-1/2	20	7-3/4	.688 - 1.250

PSW Series Station - Aluminum Enclosure

- Cast Aluminum Construction
- Not NEMA Rated

One-Speed through Five-Speed Control
With Standard Cord Grip



PSW-3

Eight Button - Three Motion plus Accessory Area

Each enclosure includes a cord grip, neoprene boots and provision for a strain relief bracket. Consult factory for accessory area switch options.

Specify legend markings at time of order to be stamped on enclosure.

***Drilling of Accessory Area may be required.
Single hole only.**

Dimensions and Weights					
Enclosure Catalog Number	Dimensions - Inches			Weight Lbs.	Accommodates Cable Diameter (Inches)
	Width	Depth	Length		
PSW-3	3.000	2-1/8	17-1/2	4-1/4	.688 - 1.250

Pictures are for illustration purposes and may not represent actual product.
Duct-O-Wire® recommends installation of an Emergency Stop on all Pendants.

